

TEMPERATURE

Sanitary Bimetal Thermometers



Hermetically Sealed Bimetal Thermometer
All Welded Construction
3/4" - 3" Tri-Clamp Fittings
2", 3", 4" & 5" Dials
Custom Ranges & Dial Configurations

Ask for Lit #SBT400

PRESSURE

Sanitary Pressure Gauges



Quick Connect Tri-Clamp Design
CIP or Washdown Proof
All Welded Construction
316ss Movement, Diaphragm and Seal
Designed to meet 3A Standards

Ask for Lit #SG1.98

Sanitary RTD's & Thermocouples



FDA Compliant Cover Heads
Fast Response
High Temperature
Designed to Meet 3A Standard #C9-08
All Welded SS Construction

Ask for Lit #SRTD50

Sanitary Pressure Transmitters



Rugged All 316ss
Construction
4-20mA, 2-Wire
Signal Output
Ranges from
Vacuum to 1000
PSI

0.5% Span Accuracy
Clean-In-Place Design

Ask for Lit #SPT600

Sanitary Thermowells



One Piece 316L Construction
1" - 3" Tri-Clamp Connections
Cherry Burrell (I-Line) Fittings
Standard & Custom Lengths
Exceeds #4 Finish Requirement by
Sanitary Council

Ask for Lit #ST400

Sanitary In-Line Diaphragm Seals



Unobstructed Flow-
Through Design
316Ls Standard
1" - 4" Pipe Sizes
6,000 PSI Maximum
Pressure

Cooling Element & Capillary Systems
Available

Tri-Clamp & ANSI Flange Connections

Ask for Lit #ILS.1296

Also: Sanitary Fittings, Gaskets, Clamps, and Other Accessories



REOTEMP INSTRUMENT CORP.

Single Source.....Simple Solution
10656 Roselle St. • San Diego, CA 92121
800/648-7737 • FAX 858/784-0720
E-Mail: reotemp@reotemp.com
Visit our website @ www.reotemp.com



Distributed by:

