

Quick Disconnect Couplings & Valves For:



- **Chemical**
- **Petrochemical**
- **Pharmaceutical**
- **Food Processing**
- **Electronics**



★ *Snap-Tite*

71 Series - Drybreak, Flush Face Couplings



Style	Double Shut-off
ISO Interchange	None
Max. Working Pressure	10,000 psi (690 bar)
Sizes Available	1/8" through 2" nominal diameter
Material	316 Stainless Steel or ⁽¹⁾ Exotic Alloy
Features	<ul style="list-style-type: none"> • Flat-face design simplifies contaminant inspection and cleaning • Flush Valve virtually eliminates fluid loss and air inclusion • Wide Variety of specialty seal options available • Sleeve-Lock option prevents accidental disconnection

25 Series - Poppet Style, Chemical Couplings



Style	Double Shut-off or Straight-Through combination
ISO Interchange	None
Max. Working Pressure	1,000 psi (69 bar)
Sizes Available	1/4" through 1/2" nominal diameter
Material	316 Stainless Steel or ⁽¹⁾ Exotic Alloy
Features	<ul style="list-style-type: none"> • Designed for difficult or aggressive media • Teflon Seals are standard • Tubular barrel valve design enhances flow rate • Sleeve-Lock option prevents accidental disconnection

K Series - Poppet Style, Cryogenic Couplings



Style	Double Shut-off or Straight-Through combination
ISO Interchange	None
Max. Working Pressure	1,000 psi (69 bar)
Sizes Available	3/8" through 2" nominal diameter
Material	316 Stainless Steel or ⁽¹⁾ Exotic Alloy
Features	<ul style="list-style-type: none"> • Cryogenic operation to -400°F/-240°C • Designed for difficult or aggressive media • Teflon or Kel F Seals are standard options • Sleeve-Lock option prevents accidental disconnection

28-1 Series - Drybreak, Low Pressure-Low Profile Couplings



Style	Double Shut-off
ISO Interchange	None
Max. Working Pressure	1,000 psi (69 bar)
Sizes Available	1/4" through 2" nominal diameter
Material	316 Stainless Steel, Aluminum
Features	<ul style="list-style-type: none"> • Recessed coupling face eases hidden connections • Lightweight, Low-profile design • Flush Valve virtually eliminates fluid loss and air inclusion • Wide variety of specialty seal options available • Color coded positive connection indicator

(1) - Specialty wetted metal parts such as Inconel, Hastelloy™, and others can be made available. Please consult factory.

- Specialty Seal options are available. See last page of brochure for chart.

- All couplings shown can be indexed (key'd) (max 6 based on size) to prevent mixing/contamination.

Poppet Style, General Purpose Couplings - H Series

Style	Double, Single Shut-off or Straight-Through combination
ISO Interchange	None
Max. Working Pressure	10,000 psi (690 bar)
Sizes Available	1/4" through 6" nominal diameter
Material	316 Stainless Steel, Aluminum, or ⁽¹⁾ Exotic Alloy
Features	<ul style="list-style-type: none"> • Optional Break-away design available • Two-piece construction expands end fitting selection • Smooth jet stream valve design lowers pressure drop • Wide variety of specialty seal options available • Sleeve-lock option prevents accidental disconnection



Poppet Style, Vacuum and Steam Couplings - E-EA Series

Style	Double, Single Shut-off or Straight-Through combination
ISO Interchange	None
Max. Working Pressure	3,000 psi (207 bar)
Sizes Available	1/4" through 4" nominal diameter
Material	316 Stainless Steel, Aluminum, or ⁽¹⁾ Exotic Alloy
Features	<ul style="list-style-type: none"> • Designed for hard vacuums down to 29.72" Hg • Excellent high temperature sealing • Two-piece construction expands end fitting selection • Wide variety of specialty seal options available • Sleeve-lock option prevents accidental disconnection



Poppet Style, ISO-B Interchange Couplings - 72 Series

Style	Double Shut-off or Straight-Through combination
ISO Interchange	ISO 7241-1 Series B (ISO B)
Max. Working Pressure	5,500 psi (380 bar)
Sizes Available	1/8" through 1" nominal diameter
Material	303 or 316 Stainless Steel or ⁽¹⁾ Exotic Alloy
Features	<ul style="list-style-type: none"> • Meets or exceeds ISO 7241-1 Series B standards • Proven ball-lock mechanism for positive connection • Wide variety of specialty seal options available • Sleeve-lock option prevents accidental disconnection



Poppet Style, Thread-to-Connect Couplings - 75 Series

Style	Double Shut-off or Straight-Through combination
ISO Interchange	None
Max. Working Pressure	1,650 psi (114 bar)
Sizes Available	3/4" through 4" nominal diameter
Material	316 Stainless Steel or ⁽¹⁾ Exotic Alloy
Features	<ul style="list-style-type: none"> • High flow chemical transfer coupling • Acme thread-to-connect design for heavy duty service • Connects under static pressure up to 1,650 psi/114 bar • Low pressure drop keeps flow rates high



(1) - Specialty wetted metal parts such as Inconel, Hastelloy™, and others can be made available. Please consult factory.
 - Specialty Seal options are available. See last page of brochure for chart.
 - All couplings shown can be indexed (key'd) (max 6 based on size) to prevent mixing/contamination.

78 Series - Drybreak, Screw-to-Connect Couplings



Style	Double shut-off
ISO Interchange	None
Max. Working Pressure	3,000 psi (207 bar)
Sizes Available	3/4" through 1-1/2" nominal diameter
Material	316 Stainless Steel
Features	<ul style="list-style-type: none"> • Interchange compatible thread-to-connect design • Connects under static pressure up to 3,000 psi (207 bar) • Bulkhead mountable nipple option available

6C & 3C Series - Inline Check Valves



Style	Soft seat, zero leakage, poppet style
Safety Factor	4:1
Max. Working Pressure	6,000 psi (414 bar)
Sizes Available	1/4" through 2" nominal diameter
Material	316 Stainless Steel or ⁽¹⁾ Exotic Alloy
Features	<ul style="list-style-type: none"> • Two-piece construction expands end fitting selection • Various crack pressures available • Flow rates to 175 gpm/662 lpm

(1) - Specialty wetted metal parts such as Inconel, Hastelloy™, and others can be made available. Please consult factory.

- Specialty Seal options are available. See last page of brochure for chart.

- All couplings shown can be indexed (key'd) (max 6 based on size) to prevent mixing/contamination.

Seal Availability

	Seal Compound	71 Series	25 Series	K Series	2&-1 Series	H Series	E-EA Series	72 Series	75 Series	78 Series	6C/3C Series
Buna N™ (-40° to 200°F/-40° to 93°C)		●			●	●	●	●	●	●	●
Ethylene Propylene (EPDM) (-65° to 300°F/-55° to 150°C)		●			●	●	●	●	●	●	●
Viton™ (-15° to 400°F/-10° to 205°C)		●			●	●	●	●	●	●	●
Teflon™ (-100° to 400°F/-75° to 205°C)			●	●							●
Kel-F™ (-400° to 400°F/-240° to 205°C)			●	●							
Kalrez™ (-4° to 500°F/-20° to 260°C)		●			●	●	●	●	●		●
Chemraz™ (-4° to 500°F/-20° to 260°C)		●			●	●	●	●	●		●

Notes:

- Wide variety of additional seal materials available. Chart provided for reference only.
- Coupling selection must assure compatibility of body and seal materials with the fluid media. Contact factory with any questions concerning specific product application needs.
- Ethylene Propylene (EPDM) is not compatible with mineral based oils/solvents.

! WARNING !

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Snap-tite, Inc., its subsidiaries and authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operation conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met.

The products described herein, including without limitation, product features, specifications, availability and pricing, are subject to change by Snap-tite, Inc. and its subsidiaries at any time without notice.



Quick Disconnect & Valve Division
 201 Titusville Road
 Union City, Pennsylvania 16438-8699 USA
 PH: 814-438-3821 FAX: 814-438-3069
 TOLL FREE: 877-758-1141
 e-mail: qd&v_sales@snap-tite.com
 www.snap-tite.com



Industrial Estate
 Whitemill - Wexford
 Republic of Ireland
 PH: 353 53 914 1566 FAX: 353 53 914 1582
 e-mail: ste_sales@snap-tite.com
 www.snap-tite.com

Distributed By:

ISO-9001 Certified